




**NEW
MONSTER**

3-PHASES

AVAILABLE IN 480 V
AVAILABLE IN 60 Hz

AVAILABLE IN
LEFT VERSION
GRT12SM



1946

GRT12M

ELECTRIC 3-PHASES CUTTING UNIT

GRT12M. The most powerful professional cutting unit for continuous cutting processes in Technical Textile & Composite applications.





ELECTRIC 3-PHASES CUTTING UNIT GRT12M



WHAT'S NEW:

Central knife guidance
Low-friction Teflon coated foot
Easy fixing structure for O.E.M.
applications
Maintenance-free industrial motor

AVAILABLE IN 480 V
AVAILABLE IN 60 Hz




sharpening device



central knife guidance

TECHNICAL DETAILS:

Blade diameter: 120 mm (4.7"), with hard metal counterblade
Blade equipped: 12SHSS, 8-edges, HSS steel
Blade speed: 400 r.p.m.
Cutting ability: up to 50 mm (2")
Motor: 3-phase asynchronous 380/400 V, 50 Hz
Power: 180 W
Max. absorption: 0.52 A
Protection: IP20 - CL F
Net weight: 4600 g (with power supply cord)
Total weight (with packing box): 6300 g
Electric cable length: 1.5 mt (with no plug)
Minimum brightness for working operations: LUX 200
Vibrations at start up: < 2.5 m/sec 2
Temperature range: 0 – 55 C
Umidity range: 10 – 95% without condensate



Dimension layout

BLADES AVAILABLE:

12SHSS, 120 mm 8-edges, HSS steel | **12CHSS**, 120 mm circular, HSS steel | **12DHSS**, 120 mm 12-edges, HSS steel | **12SHSSTF**, 120 mm 8-edges, HSS steel Teflon® coated | **12SHSSTN**, 120 mm 8-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12SMD**, 120 mm 8-edges, Carbide (Widia®)



FOLLOW US:



RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6

20161 Milan · Italy

ph. +39 02 66 22 12 31

fax +39 02 66 22 12 93

info@rasor-cutters.com

www.rasor-cutters.com