



GRT-CROSS. The first 3-phases horizontal, compact cutting unit.

GRT-CROSS

1946

WHAT'S NEW:

Horizontal motor design **Fast Cross-cut features** Central placed guiding foot Laser Marked

AVAILABLE IN 480 V AVAILABLE IN 60 Hz









TECHNICAL DETAILS:

Blade diameter: 86 mm (3.4")

Blade equipped: 86THSS, 8-edges, HSS steel

Blade speed: 550 r.p.m. Cutting ability: up to 25 mm (1")

Motor: 3phases asynchronous 380/400 V, 50 Hz

Power: 50 W


Max. absorption: 0.3 A Protection: IP65 - CL F

Net weight: 2650 g (with power supply cord) Total weight (with packing box): 4750 g Electric cable length: 1.5 mt (with no plug) Minimum brightness for working


operations: LUX 200

Vibrations at start up: < 2.5 m/sec 2 **Temperature range:** $0 - 55 \, \text{C}$

Umidity range: 10 – 95% without condensate



Dimension layout



New sharpening device system



BLADES AVAILABLE:

86THSS, 86 mm 8-edges, HSS steel | **86THSSTF**, 86 mm 8-edges, HSS steel Teflon® coated | **86THSSTN**, 86 mm 8-edges, HSS steel Titanium coated | **86CHSS**, 86 mm round, HSS steel | **86TMD**, 86 mm 8-edges, Carbide (Widia®)



FOLLOW US:









RASOR ELETTROMECCANICA SRL

Via Giannetto Mattei 41/43 20044 Arese (MI) · Italy ph. +39 02 66 22 12 31 info@rasor-cutters.com

www.rasor-cutters.com