

GRT-MINIVM. The new compact 3phase vertical 0.E.M. unit.



ELECTRIC 3-PHASES CUTTING UNIT GRT-MINIVM


WHAT'S NEW:

Central placed guiding foot Maintenance-free industrial motor Easy fixing structure for O.E.M applications Laser Marked

AVAILABLE IN 480 V AVAILABLE IN 60 Hz



Dimension layout






Central placed guiding foot







TECHNICAL DETAILS:

Blade diameter: 86 mm (3.4") Blade equipped: 86THSS, 5-edges, HSS steel Blade speed: 550 r.p.m. **Cutting ability:** up to 25 mm (1") Motor: 3phases asynchronous 380/400 V, 50 Hz **Power: 50 W** Max. absorption: 0.3 A Protection: IP65 - CL F **Net weight:** 2650 g (with power supply cord) Total weight (with packing box): 4750 g **Electric cable length:** 1.5 mt (with no plug) Minimum brightness for working operations: LUX 200 **Vibrations at start up:** < 2.5 m/sec 2 **Temperature range:** 0 – 55 C **Umidity range:** 10 – 95% without condensate

BLADES AVAILABLE:

86THSS, 86 mm 8-edges, HSS steel | **86THSSTF**, 86 mm 8-edges, HSS steel Teflon[®] coated | **86THSSTN**, 86 mm 8-edges, HSS steel Titanium coated | **86CHSS**, 86 mm round, HSS steel | **86TMD**, 86 mm 8-edges, Carbide (Widia[®])



FOLLOW US:



RASOR ELETTROMECCANICA SRL Via Giannetto Mattei 41/43 20044 Arese (MI) · Italy ph. +39 02 66 22 12 31 info@rasor-cutters.com

www.rasor-cutters.com